

# OPTIONAL LENSES

for XGA Models: S490U, X490U, X500U, XL5900U/LU, XL5950U/LU, XL5980U/LU  
 for Wide Screen Models: WL6700U/LU, FL6900U, FL7000U/LU, HD8000

## Short Throw ZOOM LENS



**OL-X500SZ**

Projection Lens	<b>F 2.0-2.3</b> <b>f 37-44 mm</b>
Picture Size	<b>60-300"</b>
Throw Ratio (XGA)	<b>1.3-1.6</b>
Throw Ratio (Wide)	<b>1.4-1.7</b>
Off-Set Axis	<b>19 up : 1 down</b>
Zoom / Focus	<b>Motorized</b>
Zoom Ratio	<b>1.2 : 1</b>
Weight	<b>3.1 lbs</b>
Length	<b>6.96"</b>
Lens Diameter	<b>3.30 "</b>

### Large screen in a small room



## Tele Throw ZOOM LENS



**OL-X500TZ**

Projection Lens	<b>F 2.5-3.4</b> <b>f 93-140 mm</b>
Picture Size	<b>60-300"</b>
Throw Ratio (XGA)	<b>3.5-5.2</b>
Throw Ratio (Wide)	<b>3.7-5.5</b>
Off-Set Axis	<b>19 up : 1 down</b>
Zoom / Focus	<b>Manual</b>
Zoom Ratio	<b>1.5 : 1</b>
Weight	<b>3.8 lbs</b>
Length	<b>8.07"</b>
Lens Diameter	<b>3.30 "</b>

### Auditorium or theater



## Long Throw ZOOM LENS



**OL-X500LZ**

Projection Lens	<b>F 2.5-3.2</b> <b>f 64-90 mm</b>
Picture Size	<b>60-300"</b>
Throw Ratio (XGA)	<b>2.4-3.3</b>
Throw Ratio (Wide)	<b>2.5-3.5</b>
Off-Set Axis	<b>19 up : 1 down</b>
Zoom / Focus	<b>Manual</b>
Zoom Ratio	<b>1.4 : 1</b>
Weight	<b>3.8 lbs</b>
Length	<b>8.03"</b>
Lens Diameter	<b>3.30 "</b>

### Display information in large room



## REAR PROJECTION Short Throw ZOOM LENS (on axis)



**OL-X500FR(F)\***

Projection Lens	<b>F 2.5</b> <b>f 22 mm</b>
Picture Size	<b>50-200"</b>
Throw Ratio (XGA)	<b>0.8</b>
Throw Ratio (Wide)	<b>0.9</b>
Off-Set Axis	<b>1 : 1 (on axis)</b>
Zoom / Focus	<b>Manual</b>
Zoom Ratio	<b>1.4 : 1</b>
Weight	<b>3.8 lbs</b>
Length	<b>6.85"</b>
Lens Diameter	<b>4.86 "</b>

### For rear projection



MITSUBISHI DIGITAL ELECTRONICS  
AMERICA, INC.

Presentation Products Division  
Phone: 888.307.0349  
Email: ppdinfo@mdea.com  
www.mitsubishi-presentations.com

  
**MITSUBISHI**  
**ELECTRIC**  
PRESENTATION PRODUCTS

MITSUBISHI ELECTRIC SALES  
CANADA, INC.

Display & Imaging Solutions Division  
Phone: 905.475.7728  
www.mitsubishelectric.ca

Specifications subject to change without notice.

\*includes optional front bezel